



2000 Series 32 Dry 'A' Contact Digital Input and 32 Voltage Keyed Digital Output Termination Panel 43743-2701

FEATURES

- Functions with 24 VDC, 48 VDC, 125 VDC, and 250 VDC systems
- Option A is compatible with all options of the 32 'A' Contact Digital Input Board (43743-1400)
- Option B is compatible with all options of the 32 Point Digital Output Board (43743-1300)
- Easily disconnected from digital input (43743-1400) and digital output (43743-1300) boards
- Terminal strips with #6-32 screws for easy wiring
- Terminal strip covers
- Terminate up to 12 gauge wire size
- Panel labeled for easy identification
- Panel rack mounted to EIA-310-C-1982
- Surge protected to ANSI/IEEE C37.90-1978 Sec. 9 SWC

43743-2701

OPTIONS

Option A:
32 Dry Digital Input

Option B:
32 Voltage Keyed Digital Output

ENVIRONMENTAL DATA

Operational Temperature: 0 to 55° C
Storage Temperature: -40 to 70° C
Humidity: 95% Noncondensing

MECHANICAL DATA

Dimensions:
5.25"Hx5.50"Dx19.00"W
Weight:
Approximately 2 lbs

DESCRIPTION

The 2000 Series 32 Dry 'A' Contact Digital Input and 32 Voltage Keyed Digital Output Termination Panel provides a convenient way of interfacing the field wiring to the 2000 Series 32 'A' Contact Digital Input Board (43743-1400) or to the 32 Digital Output Board (43743-1300).

The panel provides terminations for 32 pairs of wires for the inputs or outputs.

